

产品介绍

.

产品特点

CFR
CFR

3

4:1 18:1

6

6

WIFI

EXCEL
LIMS

KI O.N. KI

•

•

+

WIFI

CO NO SO₂ PM2.5

技术参数

GB/T 5487, GB/T 503, ASTM D2699, ASTM D2700,
IP 236 IP 237 EN ISO 5163 EN ISO 5164

40 120

82.55mm 3.250inch

114.30mm 4.50inch

0.61L 37.33in³

| |
|---------------------------------------|
| 4:1 18:1 |
| 900rpm± 9rpm 600rpm± 6rpm |
| 0.20mm ± 0.025mm 0.008in ± 0.001in |
| 0.51mm ± 0.13mm 0.020in± 0.005in |
| 172 207kPa 25psi 30psi |
| 57 ± 8 135 ± 15 |
| 100 ± 1.5 212 ± 3 |
| 149 ± 1 300 ± 2 |
| 38 ± 2.8 100 ± 5 |
| 52 ± 1 (125 ± 2) ± 1 |
| 26°btdc =5.0 13°btdc |
| USB,RS232 |
| LIMS WIFI |
| 12KW |
| 3.5KW |
| 5 35 20 90% RH |
| AC380V± 10%,50Hz AC220V± 10% 50Hz |
| 1720mm × 800mm × 1700mm |
| 1700KG |